

ABOUT US

At iElevate, we specialize in the installation, supply, and customization of elevators. Our focus extends to producing and delivering a wide range of lifts, seamlessly integrating cutting-edge technologies with various building architectures. We aim to enhance the experiences of both occupants and visitors through our commitment to innovation.

THE ZEROPIT

Introducing "THE ZEROPIT" residential lifts, minimizing construction needs for swift and easy installation. These elevators provide a quicker alternative to traditional ones, adhering to European and Indian standards. Custom dimensions cater to diverse spaces, ensuring suitability for both indoor and outdoor environments.



CONTACT US

CUSTOMER CARE : +91 88823 35555

PHONE : +91 90850 44444, +91 70655 71414

E-MAIL : contact@ielevate.co.in

WEBSITE : www.ielevate.co.in

ADDRESS : Khasra No- 1200 Ground Floor, Rithala, Delhi - 110085
(Near Rithala Metro Station)

OFFICES AT : DELHI-NCR || NORTH-EAST || WEST BENGAL



THE ZEROPIT

Home Elevators by



HIGHLIGHTING THE **CORNERSTONE** FEATURES

▲ NO PIT

Our Home elevators do not require a pit of more than 150 to 250mm

▲ NO MACHINE ROOM

As per machine directive code, Machine room should never be placed inside the elevator shaft

▲ NO HEAD ROOM

Headroom is meant for commercial elevators. We require an FFL- Ceiling of only 2500mm

▲ NO GOVERNMENT LICENSE

No government license is required as we consume only single phase electricity power

▲ NO NOISE

Our home lift operates seamlessly, ensuring a noise-free experience for your tranquility

▲ NO JERK

Say goodbye to jerky rides , experience a consistently smooth and comfortable journey

▲ NO CIVIL WORK

Enjoy the convenience of our home lift with no civil work required, making the process simple and efficient for your home

TAKING YOU HIGHER **TOGETHER!**

IF A SECURE **HOME ELEVATOR** IS YOUR PRIORITY THEN HERE'S A MODEL THAT ALIGNS TO BOTH EUROPEAN AND INDIAN SAFETY STANDARDS



Technical Compliance	Machine Directive 2006/42/EC En81 - 41
Drive System	Gearless With Belt Drive
Rated Speed	0.50 m/s Up To 1.00 m/s
Rated Load	Up To 400kg
Travel Height	Up To 18,000mm
Number Of Stops	Max. 6 Stops Per Lift
Number Of Doors	Max. 12 Doors Per Lift
Pit	160mm (No Pit is Required in Case of Threshold/Ramp)
Shaft Top Height	2700 mm in Existing Shafts/ 2800 mm With its Own Shaft
Platform Control	Automatic (One Touch) With Call Reservation
Environment	Indoor/Outdoor
Emergency Lowering	Battery Operated Emergency Lowering
Control Voltage	24V